



SPECIFICATION FOR
COVENANT SECURITY EQUIPMENT
BULLET RESISTANT/ FIRE CLASSIFIED
PACKAGE PASSERS

PART I GENERAL

1.1 Scope of Work

- A. The work required for this section includes furnishing and installing the dual rated bullet resistant, fire classified package passer(s) of the sizes, types and quantities indicated in the project drawings.
- B. The bullet resistant package passer(s), accessories and hardware shall be provided such that the entire assembly be UL Listed and bear a Dual UL Label for the **(specify ballistic threat level here,)** *Available Ballistic Levels for this product line : Level 1, 9mm, Level 2, 357 magnum, Level 3, 44 magnum* as defined by the Standard of Safety UL 752 Bullet Resisting Equipment and the Fire Classification **(specify fire classification here,)** *Available Fire Classifications for this product line : ~D' 20 min, `C' 45min, `B' 1-1.2Hr, `A' 3 Hr* as per testing as per UL 0B.

1.2 Approval Drawings

- A. The manufacturer shall provide the owner with approval drawings that sufficiently indicate sizes, details and installation procedures for the bullet resistant door and frame assemblies required.

PART II PRODUCTS

2.1 Bullet Resistant Package passers

- A. Materials – All bullet resistant doors will be manufactured from Balistex® bullet resistant steels in accordance with UL 752 and UL 10B.
- B. Construction –
 - 1. The door panels shall be manufactured straight, true and square.
 - 2. Housing assembly shall be welded.
 - 3. Product finish shall be prime painted. (Note to architect/specifier; Available finishes also include #4 brushed stainless steel or prime painted housing with stainless steel doors and trim).

4. The manufacturer shall prepare and provide the appropriate interlock system to prevent both doors from being open simultaneously.
5. The Package passer housing shall have a fixed four sided exterior trim frame and a clamping type three sided interior trim frame.
6. Each door shall be equipped with a door pull per as per the manufacturer's standard design.

Optional Dual Rated Package Passer Hardware

- Exterior or interior door locking handle
- Exterior or interior door latch
- Door closer on exterior or interior door
- Integral flush pulls for detention applications

PART III EXECUTION

3.1 Installation

- A. Install all dual rated package passers and accessories in accordance with the approved shop drawings, manufacturer's written instruction and as herein specified.

3.2 Adjust and Clean

- A. Immediately after erection, sand smoothly any rusted or damaged areas of the prime coat and apply touch up of compatible air drying primer.
- B. Check and re-adjust operating finish hardware items, leaving product and proper operating condition.